

**ERRATA SHEET FOR THE USER'S MANUAL TO
ANSI/ASHRAE/IES STANDARD 90.1-2010 ENERGY STANDARD FOR
BUILDINGS EXCEPT LOW-RISE RESIDENTIAL BUILDINGS**

December 20, 2011

The corrections listed in this errata sheet apply to all copies of the ANSI/ASHRAE/IES Standard 90.1-2010 User's Manual. The first printing is identified on the outside back cover as "Product code: 90327 1/11.

| <u>Page(s)</u> | <u>Erratum</u> |
|----------------|---|
| 9-2 | Lighting Alterations (9.1.2). At the top of the second column change <i>Example 8-A and Example 8-B</i> to <i>Example 9-A and Example 9-B</i> . |
| 9-3 | Installed Lighting Power (9.1.3). In the second paragraph of the first column change "...exceptions to 9.4.5" to "...exceptions to 9.4.3". |
| 9-8 | Exterior and interior lighting power trade-offs. At the top of the first column change Table 9.4.6 to Table 9.4.3B. |
| 9-8 | Lighting in multi-building facilities. In the first column change Table 9.4.6 to Table 9.4.3B. |
| 9-8 | Garages and parking areas. In the last sentence of the second column change (Table 9.4.6) to (Table 9.4.3A). |
| 9-12 | Occupant Sensors. Change the first sentence of the first paragraph as follows: (<i>Note: Deletions are shown in strikethrough.</i>) Occupant sensors are automatic scheduling devices that detect motion and turn lights on and off accordingly. |
| 9-28 | Example 9-O Exterior Building Lighting Power Allowance, Building Façade. At the top of the page change the building height in the drawing from 100 ft (30.5 m) to 60 ft (18.3 m). |